

ANNEXURE-VIII

<i>S.N</i>	<i>Description</i>	<i>Specification for indent</i>
S. Main Hook Block		
1	Capacity (SWL)	SWL shall be More than 175 Te
2	No of Sheaves	Vendor to specify
3	Type of Sheaves	Vendor to specify
4	Maximum No of Falls	Vendor to specify
5	Type of Hook	Rams-Horn Type
T. Additional Hook Blocks		
6	Hook Block with sheaves with SWL between 45 % and 55 % of the SWL of the crane	Required
	No of Sheaves	Vendor to specify
	Type of Sheaves	Vendor to specify
	Maximum No of Falls	Vendor to specify
	Type of Hook	Swivel type
7	Hook Block with sheaves with SWL between 20 % and 30 % of the SWL of the crane	Required
	No of Sheaves	Vendor to specify
	Type of Sheaves	Vendor to specify
	Maximum No of Falls	Vendor to specify
	Type of Hook	Swivel type
8	Hook without sheaves (for single fall) of SWL not less than 8 Te	Required, Swivel type
U. Overall Dimensions		
1	Length	Vendor to Specify
2	Width	Vendor to Specify
3	Height	Vendor to Specify
4	Weight	Vendor to Specify
5	Minimum Ground Clearance	Vendor to Specify